

CNC ROUTER- DOUBLE SPINDLE P-SD-1325

TM

printo



DOUBLE SPINDLE LEFT AND RIGHT

APPLICABLE INDUSTRIES

Wood Processing Of Various Furniture Such As Doors, Windows, Cabinets, Craft,
Advertisement : Engraving And Cutting Various Labels, Mementos and Number Plate.

DESCRIPTION	PARAMETER
X,Y,Z Working Area Each X,Y,Z Working Area	1300x2500x300mm
Table Size	1325x1320x3040mm
X,Y,Z Traveling Positioning Accuracy	0.05/300mm
X,Y,Z Repositioning Positioning Accuracy	0.05mm
Table Surface	T-slot table (Option:bakelite Vacuum table)
Frame	Welded structure
X, Y Structure	Rack and Pinion Drive,Hiwin Rail Linear Bearings
Z Structure	25mm thick Ball Screw, Hiwin Rail Linear Bearings
Max.Power Consumption	(Without spindle) 3.0Kw
Max.Rapid Travel Rate	37000mm/min
Max.Working Speed	30m/min
Spindle Power Motor	2.2KW (3.0Kw water cooling spindle, or 3.5 kw italian Air Cooler)
Spindle Speed	0-24000RPM
Drive Motors	Stepper
Working Voltage	AC220V/50/60Hz,3PH (Option: 380V)
Command Language	G Code
Operating System	N.C STUDIO (D.S.P Handle)
Flash Memory	128M(U Disk) D.S.P
Collet	Er20
X,Y Resolution	<0.02mm
Running Environment Temperature	Relative humidity: 30%75%
Gross Weight	1200KG



An ISO 9001:2008
Certified Company

HO : 132/4, King Avenue, Modachur, Tirupur Main Road, Gobichettipalayam,
Erode Dt., Tamilnadu - 638 476. E-mail : printo_99@yahoo.com

Web : www.princnc.com | www.cncprinto.com

Mobile : +91 98426 74050, +91 98422 88171 | Sales : +91 73737 74050

Br : No:1, 3rd Cross, Ialbagh road, Bangalore - 560 027.

PH : 080 - 22276413, 22236641 Mobile : +(91) - 9739762378, 8050783020



*Subject to Technical Changes