

TM
printo

CNC ROUTER P-SO-1325

▶ VACUUM PAD



▶ TAIWAN HIWIN BALLS SCREW



▶ TAIWAN HIWIN RAILS & BLOCK



▶ DSP HANDLE



APPLICABLE INDUSTRIES

Wood processing of various furniture such as doors, windows, cabinets, craft, advertisement, engraving and cutting various labels, mementos and number plate.

DESCRIPTION	PARAMETER
X,Y,Z Working Area	1300x2500x300mm
Table Size	1320x3040mm
X,Y,Z Traveling Positioning Accuracy	0.05/300mm
X,Y,Z Repositioning Positioning Accuracy	0.05mm
Table Surface	T-slot table (Option:bakelite Vacuum table)
Frame	Welded structure
X, Y Structure	Rack and Pinion Drive,Hiwin Rail Linear Bearings
Z Structure	25mm thick Ball Screw, Hiwin Rail Linear Bearings
Max.Power Consumption	(Without spindle) 3.0Kw
Max.Rapid Travel Rate	37000mm/min
Max.Working Speed	37m/min
Spindle Power Motor	3.0Kw water cooling. Spindle
Spindle Speed	0-24000RPM
Drive Motors	Servo
Working Voltage	AC220V/50/60Hz,3PH (Option: 380V)
Command Language	G Code
Operating System	N.C STUDIO Option D.S.P Handle
Flash Memory	128M(U Disk) D.S.P
Collet	Er20
X,Y Resolution	<0.02mm
Running Environment Temperature	Relative humidity: 30%75%
Gross Weight	± 1200KG

FEATURES

- ▶ Whole machine is welded with seamless steel structure
- ▶ The stability is excellent, not easy to be deformed well compatibility
- ▶ CAD/CAM designing software e.g. type 3 / castmate / wentai etc.,
- ▶ Adopting water cooling system. It can provide good cooling effect when carving finity materials.
- ▶ Advanced design of the machine make sure strong cutting and guarantee the engraving precision



An ISO 9001:2008
 Certified Company

HO : 132/4, King Avenue, Modachur, Tirupur Main Road, Gobichettipalayam,
 Erode Dt., Tamilnadu - 638 476. E-mail : printo_99@yahoo.com

Web : www.princnc.com | www.cncprinto.com

Mobile : +91 98426 74050, +91 98422 88171 | Sales : +91 73737 74050

Br : No:1, 3rd Cross, Ialbagh road, Bangalore - 560 027.

PH : 080 - 22276413, 22236641 Mobile : +(91) - 9739762378, 8050783020

